





DUS360CR-DALI Multifunction Sensor

Low profile 360° ceiling sensor powered by the DALI network

The DUS360CR-DALI is a recess mountable 360° multifunction sensor that combines motion detection (PIR), Infrared remote control reception (IR) and ambient light level detection (PE) into one device. The DUS360CR-DALI is powered and communicates with the network control system via a DALI bus.

- Powered directly by the DALI network — Eliminates the need for additional network field wiring.
- Motion detection feature — Detects the presence or absence of motion and adjusts lights accordingly.
- 120° PIR Shield — Surrounds the motion sensor element and enables a portion of the sensing field to be masked. This prevents nuisance detection from adjacent doorways or corridors.
- Ambient light level detection and daylight harvesting — In applications where it is critical to maintain precise light, the PE function reads ambient levels and adjusts artificial light accordingly.
- Infrared receive capability — Manually adjust light levels using a hand-held remote control, via the inbuilt IR receive sensor of the DUS360CR.
- Daylight Harvesting mode — Delivers automatic energy savings.
- Suitable for plenum use — UL approved for installation in air-handling plenum spaces..




For detailed product information, please refer to the product information pages at www.lighting.philips.com/dynalite and follow the links.

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Item	Specification	Details
Hardware	Motion Detector	Standard sensitivity Maximum detection range: 5 m Detection area*: 7.4 m x 5.6 m rectangular (at a height of 2.4 m) Detection speed: 1.0 m/s Detection object: 700 mm x 250 mm Detection zones: 64 Red LED activation indicator Sensor: Quad element pyroelectric * Detection area may be reduced in ambient temperatures > 30° C (86° F)
	PE Cell	Range <5 lux to >5000 lux Automatic 'Daylight Harvesting' mode
	Controls	Infrared receiver (supports RC5 IR remote control) Service switch Red LED indicator
	Terminals	2 way terminal strip, loop in, loop out 1 x 5 mm ² max conductor size
	Control Bus	DALI bus with a Philips Dynalite MultiMaster controller
	DALI Power Consumption	9 mA (total 10 user interfaces on one DALI universe)
Network	Configuration	All functions remotely programmable
Physical	Dimensions	72 mm dia. x 41 mm (2.8 in dia. x 1.6 in)
	Packed Weight	105 g (0.23 lb)
	Construction	Polycarbonate plastic enclosure Color: off-white
	Operating Conditions	Temperature: 0 to 45° C (32 to 104° F) ambient Humidity: 0 to 90% non-condensing
	Storage & Transport	Temperature: -25 to 70° C (-13 to 158° F) ambient Humidity: 0 to 90% non-condensing
	Mounting Substrate Thickness	3 - 25 mm (0.12 - 1 in)
Certification	Certification	cULus, CE, RCM, FCC, RoHS, ICES-003
Options & Ordering	Standard Product	DUS360CR-DALI (Philips 12NC: 913703500909)

Lens Pattern



Philips Dynalite
 6 / 691 Gardeners Road
 Mascot, NSW 2020
 Australia
 Tel: +61 2 8338 9899
 Email: dynalite.info@philips.com
 Web: www.lighting.philips.com/dynalite

Specifications subject to change without notice. © WMGD Pty Ltd Trading as Dynalite. Unit 6, 691 Gardeners Road Mascot 2020 Australia. ABN 33 097 246 921. All rights reserved. Dynalite, DyNet and associated logos are the registered trademarks of WMGD Pty Ltd. Not to be reproduced without permission.