

HH17IR

iLight Infra-Red Handset

Key Features

- 8 scene buttons
- Off button
- Raise and lower controls
- 6 additional configurable buttons
- LED indication when button is depressed and the IR command is being sent
- Uses standard RC5 IR codes
- Up to 15m range
- CE compliant to all relevant standards
- Designed and manufactured to ISO9001:2015 standards

Electrical Data

3Vdc, 2 x AAA batteries (included)

Mechanical Data

Ergonomic black plastic case with rear battery compartment cover.

Environmental Data


Temperature Range: 0°C to +40°C Humidity: 5 - 95% non condensing

Overview

The iLight infrared handset enables scenes to be selected remotely via an iLight control plate IR receiver or NS3-C network sensor. This stylish remote control offers the selection of eight scenes, off, raise and lower as well as six additional configurable buttons used to extend the capability of the remote to control extra scenes or third party devices such as curtains and blinds (action configured within iCANsoft).



Dimensions





Contact your local Eaton office

T: +44 (0)1923 495495 F: +44 (0)1923 228796 E: enquiries@iLight.co.uk www.iLight.co.uk

Eaton Lighting Systems 20 Greenhill Crescent, Watford Business Park, Watford, Herts, WD18 8JA. UK eatonlightingsystems.com

© 2018 Eaton All Rights Reserved

Document No: HH17IR Rev5 0318

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and

Eaton is a registered trademark

All other trademarks are property of their respective owners



