

# PDFMMINIL

## 360° Flush Mount Linkable Mini PIR Sensor

### Features & Benefits

- Designed For Corridor and Multi-Zone Use
- Mini unobtrusive design
- 360° Detection
- Twist & Lock Design For Easy Access
- Up To 5 Slaves Can Be Added To 1 Master. Pre-Wired RJ11 Plug-in Slave Units For Quick Installation
- LUX Adjustment
- Time Adjustment For Slave Units Set Via Master Only
- Termination Box For Ease Of Wiring
- Masking Kit Included
- LED movement indicator



### Technical Data

<b>Operating Voltage</b>	230V AC
<b>Frequency</b>	50Hz
<b>Installation Type</b>	Flush Mount
<b>Earth Class Rating</b>	Class II (Power Box), Class III (PIRs)
<b>Operating Temperature</b>	-20°C to 40°C
<b>Ingress Protection Rating</b>	IP40
<b>Setting Type</b>	Dial
<b>Approved Mounting Height (m)</b>	2.5
<b>Presence Detection (m)</b>	3 Diameter
<b>Motion Detection (m)</b>	8 Diameter

<b>Detection Angle</b>	360°
<b>Hole Cut-Out Size (mm)</b>	40
<b>Standby Consumption</b>	<0.5W
<b>Number Of Channels</b>	1
<b>Switch Rating</b>	250W LED/CFL/Fluorescent, 2300W Halogen
<b>ON Time Adjustment</b>	30 Sec, 2m, 5m, 10m, 15m, 30m. User Adjustable
<b>LUX Level</b>	10 to 2000
<b>Detection Range (m)</b>	8 Diameter
<b>Permanent ON Facility</b>	Yes (Pulse Override)
<b>Dusk Till Dawn</b>	No
<b>Multiple Unit Support</b>	Up to 5 PDFMMINILS (Slave PIRs)
<b>Cable Entry(s)</b>	Side Entry (Power Box)

## General

<b>Weight (g)</b>	140
<b>Height (mm)</b>	PIR 47, Power Box 35
<b>Width (mm)</b>	PIR 47, Power Box 175
<b>Depth (mm)</b>	PIR 64, Power Box 35
<b>Body Construction</b>	Polycarbonate
<b>Product Colour</b>	White
<b>Accessories (Optional)</b>	PDFMINILS (Slave PIR)
<b>EAN Number</b>	5012483014011
<b>Guarantee Period</b>	3 Years
<b>Trade Tariff Commodity Code</b>	8536508090

## Line Diagrams

